

# The Bolt Breaker™

Patent Pending

MADE IN THE USA

Ergonomically designed tool that not only decreases the hazards associated with using power tools to cut off anchor bolts but also decreases the the time it takes to accomplish the same task.

For order information contact us at:

[www.productdesignspeialties.com](http://www.productdesignspeialties.com)

or give us a call @ 503-629-8613

## Instruction Sheet

Step 1. Slide Bolt Breaker over anchor bolt



Step 2. Make sure Bolt Breaker is resting on concrete prior to starting the break off procedure.



Step 4. Move Bolt Breaker back and forth, then in a circular motion until bolt breaks free.



Step 3. Establish an Ergonomically comfortable position



Step 5. Remove broken anchor from the end of the Bolt Breaker.



Step 6. Floor should now be ready to patch.

**WARNING: READ ALL INSTRUCTIONS BEFORE USING THIS TOOL AND ALWAYS WEAR EYE PROTECTION AND PROPER FOOTWEAR**

# SAFETY WARNING & CAUTION

The "Bolt Breaker" is an ergonomically designed tool that can cleanly break off anchor bolts flush with the concrete so that the remaining part of the anchor can be smoothly patched over without any additional prep work required. By using this tool, the bolt breaking process can be done in a fraction of the time of other known methods.

This tool eliminates the need for the use of abrasive cut-off wheels, hammers or any other type of make-shift device that is normally used for this process. Each unit comes standard with two replaceable inserts (for 1/2" and 3/8" anchor bolts) and is available in either a long or short version. Additional inserts are available for bolt sizes 1/4", 5/8" and 3/4".

## SAFETY WARNING & CAUTION:

**READ ALL TOOL SPECIFIC INSTRUCTIONS BEFORE USING THIS TOOL**

**WEAR EYE, HAND AND FOOT PROTECTION**

**DO NOT OVERREACH WHEN USING THIS TOOL**

- Never extend the tool further than the length of your arms

**KEEP PROPER FOOTING AND BALANCE AT ALL TIMES**

- Never push or pull the tool with a force that would allow you to fall when the bolt breaks

**RECOVER BROKEN ANCHOR BOLT AND DISPOSE OF PROPERLY**

- Broken off anchor bolts create an immediate trip or fall HAZARD

**Safe  
Ergonomic  
Clean  
and Fast**



1. Unscrew cap from top of handle.

2. Retrieve desired insert and allen wrench from inside the handle.



3. Loosen both set screws.



4. Remove existing insert from end of Bolt Breaker.

Contact info:

5. Insert desired insert.



6. Re-tighten both set screws.

### Disclaimer:

The Manufacturer or any affiliates associated thereof are not responsible or liable in any way for accidents related to the misuse, improper storage, or any other circumstance that exist which may or has resulted in injury to person, loss of revenue, damage to property, equipment or bystander by the use of this tool.